



Product Information Sheet

SYNSTAR FULL SYNTHETIC GEAR LUBE 75w90

DESCRIPTION:

A fully synthetic based gear lubricant that is specially formulated for extended drain and severe service in heavy duty, extreme pressure applications.



Synstar Full Synthetic Gear Lube is formulated with fully synthetic base oils that provide excellent shear stability, outstanding oxidation resistance and tremendous cold flow characteristics. The additive system contains extreme pressure agents and rust and corrosion inhibitors. Commercial Full Synthetic Gear Lube is formulated to control seal swell and prevent seal deterioration and degradation.

The high and low temperature performance of Synstar Full Synthetic Gear Lube exceeds the performance of conventional, mineral oil based gear oils. The synthetic base oils provide the opportunity for maximum fuel economy savings, especially at low ambient temperatures.

APPLICATION:

Synstar Full Synthetic Gear Lube meets or exceeds all performance requirements for:

- API Service GL-5 and MT-1.
- Mack GO-J+
- Rockwell International 0-76-E
- Eaton Axle Division PS-037, PS-163 and PS-109
- MIL-L-2105D
- MIL-PRF-2105E
- Axle Division Dana Corporation
- Extended warranty coverage at Eaton



FEATURES AND BENEFITS:

Superior high and low temperature characteristics allow long drains, excellent performance and reduced maintenance cost even at severe operating temperatures.

Maximized fuel economy due to reduced friction and improved fluid flow.

Synstar Full Synthetic Gear Lube Typical Properties

	API Gravity	Pour Point, °F	Flash Point, °F	Viscosity Index	cSt at 40°C	cSt at 100°C
SAE 75W-90	25.2	<-45	400	147	122	16.6

Typical properties reflect general characteristics, not manufacturing specifications. Variations should be expected.

HEALTH & SAFETY:

A complete Material Safety Data Sheet is available upon request. Used oil contains by-products which may be harmful. Avoid prolonged or repeated skin contact. Wash clothing and exposed areas with soap and water. Don't pollute - return used oil to a collection center.